

# Technical Data Sheet

## Nawkaw Li-THX

*Lithium-Thick Stain for Masonry and Concrete*

# Nawkaw

Changing the color of masonry

Official supplier of Reckli formliners



### DESCRIPTION

Nawkaw Li-THX is the thicker version of our NEW lithium stain for concrete and masonry surfaces. It has the ability to penetrate and bond to any concrete or masonry surface and has a more paint-like appearance, for those times when you may want to hide slight surface details or imperfections.

### COVERAGE / TREATMENT YIELD\*

250-300 sq ft per gallon

### APPLICATION

- Coverage rate will vary with concrete quality and finish

### RECOMMENDED FOR

- Brick
- Concrete
- Concrete Block
- Tilt-Up Construction
- Precast Panels

### DRYING TIME

1-2 hours

### PHYSICAL PROPERTIES

- Form viscous liquid, color matches label
- Total Solids 36-40 % Specific Gravity: 1.15 - 1.17
- pH 11
- Film yes
- Flash Point: None
- 20% Recycled Glass Content
- V.O.C. Content Less than 50 g/L
- Freeze point 32° F (0° C)
- Abrasion Resistance excellent
- Depth of Surface Penetration 2-8mm (non pigment chemistry)
- Shelf Life 6 months in factory sealed container

